

EclExpo Flood150VW

150W asymmetric LED floodlight, with Variable White CCT 2,700K - 6,500K

ORDER CODE: **ECLEXPFL150VWBK**



The **EclExpo** Flood150 is a compact, bright, and versatile floodlight that is designed to be a substitute for traditional CDM, HMI, and tungsten small floods in tradeshow, theaters, or as a work light. Just like its classic predecessors, but with a custom LED source, this unit features a linear light source combined with a reflector, which ensures a wide coverage of 100° (Horizontal) x 60° (Vertical) of indirect light emission.

The **EclExpo** Flood150 is available in two source variants:

- FC, which utilizes RGB+WarmWhite calibrated LED with high Color Rendering.

- VW, which uses a bi-color Vari White LED source with a CCT range of 2,700K-6,500K.

This unit is incredibly user-friendly, offering immediate stand-alone access through the knobs or through wired DMX/RDM or Wireless CRM (optional). Timeless Elegance meets Green Innovation: The **EclExpo** Flood150 - Where Classic Beauty Embraces Modern Technology

MAIN FEATURES

- 150W Variable White LED source, from 2,700K to 6,500K
- Asymmetric beam angle of 100° (horizontal) x 60° (vertical)
- Xlr5p in/through for DMX/RDM control and communication, optional W-DMX + CRMX, Stand-Alone mode through two rotatory knobs

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 150W Variable White LED
- CCT: 2.700 K - 6.500 K
- Luminous flux: @2.700K 6'956 lm; @6.500K 9'733 lm; @full 8'598
- Lux: @2.700K 72 lx; @6.500K 99 lx; @full 91lx @5 m
- CRI: 95,1 @2.700 K; 95,3 @6.500 K; 94,4 @full
- R9: 95 @2.700 K; 88,4 @6.500 K; 80,7 @full
- TLCI: 97 @2.700 K; 96 @6.500 K; 98 @full
- TM30 Rf: > 94 @2.700 K; > 90 @6.500 K; > 92 @full
- TM30 Rg: < 101 @2.700 K; < 99 @6.500 K; < 102 @full
- Source life expectancy: > 20.000 h

OPTICS

- Optics: asymmetrical beam reflector in pure aluminium 99,6%
- Beam angle: (H) 100° x (V) 60°

COLOUR SYSTEM

- Colour mixing: tunable white
- CCT: CCT control through dedicated DMX channel
- White presets: 2.700 K - 6.500K
- Colour wheel: built-in white presets

DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer
- Static mode: selection of static dimmer and color temperature
- Manual mode: manual adjustment of intensity and CT from knob
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast magnesium body
- Body colour: RAL 9004
- Other: see available accessories

CONTROL

- Protocols: DMX512, RDM, CRMX
- Stand Alone: 2 rotatory knobs
- DMX channels: 1 / 2 / 3 / 5 / 11channel

- Wireless Control: optional, LumenRadio Timo Fx DMX/RDM compatible with both CRMX (Lumen Radio) and W-DMX (Wireless DMX)
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOXPRO/UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: -10° ~ +45°
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 175W
- Standby power: 110V (60Hz): 2,5W; 230V (50Hz): 4,5W
- Output (at 230V): 7 units on a single power line
- Power factor: > 0,99
- Inrush current: 110V (60Hz): 5,2A; 230V (50Hz): 7,8A

PHYSICAL

- IP rating: 20
- Cooling: active, silent operation
- Suspension and fixing: bracket for hanging and positioning
- Signal connection: Amphenol XLR 5p IN/OUT connectors
- Power connection: Seetronic powerCON TRUE IP65 IN/OUT
- Dimensions (WxHxD): 283x273x176mm / 11.14"x10.75"x6.93"
- Weight: 3,2kg / 7.05lbs

CERTIFICATIONS / APPROVALS


- Certifications / Approvals: CE, UKCA, RCM, cTUVus, FCC

ACCESSORIES & RELATED PRODUCTS


▪ FCLEXPOFL150	Flight case for 6 pcs of ECLEXPOFL150 series	▪ 9533FXWL03	Ass. 3x2.5mm TH07 cable, SCHUKO plug, MENAC3FXW socket, L.3 m
▪ ECLEXPOFL150FFBK/WH	Filter frame for ECLEXPOFL150, black/white finishing	▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
▪ ECLEXPOFL150BDBK/WH	Barndoor for ECLEXPOFL150, black/white finishing	▪ 9513FXWL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FXW socket, L.3 m
▪ ECLEXPOFL150WKK/WH	CRMX Timo Fx kit for ECLEXPOFL150, black/white finishing	▪ 958225L03	3x2.5mm TH07 Cable, 16A 3p PwCon MXW, 16A 3p PwCon FXW, L. 3m
▪ SPGM10	28mm spigot for fixtures, M10 bolt	▪ TOUR53415L03	Dmx cable HC5340. CANC5MXXLXR 5p->CANC5FXX LXR (f) 5p, L.3m
▪ SPGM12	28mm spigot for fixtures, M12 bolt	▪ LRLUNA	Single Universe DMX transceiver with Bluetooth
▪ UPBOX1UP5	Firmware uploader kit, USB IN, 5pin XLR DMX OUT, USB OUT		
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black		

PRESET FULL ON

Beam angle 50%: 65,2°



TECHICAL DRAWINGS



CERTIFICATIONS / APPROVALS



Conforms to UL STD. 1573
Certified to CSA STD: C22.2 NO. 166

Visit our website
for specifications and
tech documentations

