

# FlatCob 80UV

80W UV high-power COB LED source

ORDER CODE: **FLATCOB80UV**

TRIBE



**FlatCob 80UV** is a compact LED projector equipped with a COB source that allows for the placing of a bright UV 80W LED in a super-slim housing. The light source features 60° beam angle with a magnetic lens holder (included) to switch the projection at 30°. **FlatCob 80UV** can be controlled wirelessly through the optional USB WIFI transceiver in combination with WIFIBOX and the SmartColor app or through IR remote.

## MAIN FEATURES

- 80W UV high-power LED
- LED + parabolic reflector featuring classic PAR CAN concept applying new LED technology
- Interchangeable optics: 60° without optics, 30° included
- Silent operation and HD dimming system with adjustable PWM for studio application
- USB port for USB WIFI transceiver (optional)

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 80W UV LED
- Luminous flux: 44,5 lm
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 16° - 40°
- Field angle: 31° - 92°
- Lens type: reflector with collimator to achieve asymmetric beam diffusion
- Additional optics: 30° (inc)

### DYNAMIC EFFECTS

- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of dimmer and strobe

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512
- DMX channels: 1 / 5 channel
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- Display: LED display user interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX2) not included
- IR: infrared sensor controlled by remote
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 28 Hz, electronic
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 65W
- Max power consumption (at 120V): 65,5W
- Output (at 230V): 20 units on a single power line
- Output (at 120V): 10 units on a single power line

### PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 200x162x230 mm
- Weight: 2 kg

## ACCESSORIES & RELATED PRODUCTS

- WIFIBOX USB Wi-Fi transceiver, compatible with WIFIBOX and WDBOX
- WIFIBOX DMX controller interface, Wi-Fi/DMX IN, Wi-Fi / DMX OUT
- WDBOX Wireless DMX Transceiver, IN/OUT 3-pin XLR, distance 200m, 2.4 GHz, 0.6 kg

- LUMIPARIRCH RGBWA IR remote controller, manual / auto modes, for LUMIPAR IR series
- UPBOX1U Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT